

Version: 1.0.0

SECTION 1: IDENTIFICATION

Product Identifier Product Name: Salt Off Concentrate Product Code: 7-1031, 7-1032, 7-1033, 7-1340 Intended Use of the Product Use of the Substance/Mixture: Cleaner. Name, Address, and Telephone of the Responsible Party Company DONOVAN MARINE INC. 6316 Humphries Street New Orleans, LA 70123 1-800-347-4464 Emergency Telephone Number Emergency Number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture Classification (GHS-US) Not applicable Label Elements GHS-US Labeling Not applicable Other Hazards Aquatic Acute 3

H402 - Harmful to aquatic life.

P273 - Avoid release to the environment.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>			
Name	Product Identifier	% (w/w)	Classification (GHS-US)
Sulfonic acids, C14-16-alkane hydroxy and	(CAS No) 68439-57-6	1 - 4	Skin Irrit. 2, H315
C14-16-alkene, sodium salts			Eye Dam. 1, H318
			Aquatic Acute 2, H401
Diethylaminoethanol	(CAS No) 100-37-8	< 1.5	Flam. Liq. 3, H226
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation:dust,mist), H332
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
			STOT SE 3, H335
			Aquatic Acute 3, H402

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

01/21/2015 IETTT.CONC.B-CC

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: May cause slight irritation to eyes, respiratory tract, and/or skin.

Inhalation: May cause irritation to the respiratory tract.

Skin Contact: May cause mild skin irritation.

Eye Contact: May cause slight irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Not available

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: None known.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sodium oxides. Sulfur oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. **Incompatible Materials:** Strong oxidizers.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Specific End Use(s)

Cleaner.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters			
Diethylaminoethanol (100-37-8)			
Mexico	OEL TWA (mg/m³)	50 mg/m ³	
Mexico	OEL TWA (ppm)	10 ppm	
USA ACGIH	ACGIH TWA (ppm)	2 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	50 mg/m ³	
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm	
USA IDLH	US IDLH (ppm)	100 ppm	
Alberta	OEL TWA (mg/m³)	9.6 mg/m ³	
Alberta	OEL TWA (ppm)	2 ppm	
British Columbia	OEL TWA (ppm)	2 ppm	
Manitoba	OEL TWA (ppm)	2 ppm	
New Brunswick	OEL TWA (mg/m³)	9.6 mg/m ³	
New Brunswick	OEL TWA (ppm)	2 ppm	
Newfoundland & Labrador	OEL TWA (ppm)	2 ppm	
Nova Scotia	OEL TWA (ppm)	2 ppm	
Nunavut	OEL STEL (mg/m³)	96 mg/m ³	
Nunavut	OEL STEL (ppm)	20 ppm	
Nunavut	OEL TWA (mg/m³)	48 mg/m ³	
Nunavut	OEL TWA (ppm)	10 ppm	
Northwest Territories	OEL STEL (mg/m³)	96 mg/m ³	
Northwest Territories	OEL STEL (ppm)	20 ppm	
Northwest Territories	OEL TWA (mg/m³)	48 mg/m ³	
Northwest Territories	OEL TWA (ppm)	10 ppm	
Ontario	OEL TWA (ppm)	2 ppm	
Prince Edward Island	OEL TWA (ppm)	2 ppm	
Québec	VEMP (mg/m ³)	48 mg/m ³	
Québec	VEMP (ppm)	10 ppm	
Saskatchewan	OEL STEL (ppm)	4 ppm	
Saskatchewan	OEL TWA (ppm)	2 ppm	
Yukon	OEL STEL (mg/m³)	50 mg/m ³	
Yukon	OEL STEL (ppm)	10 ppm	
Yukon	OEL TWA (mg/m³)	50 mg/m ³	
Yukon	OEL TWA (ppm)	10 ppm	
Exposure Controls			

Exposure Controls

Appropriate Engineering Controls: Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Hand Protection: Wear chemically resistant protective gloves. Eye Protection: Chemical goggles or face shield.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2-1992 or MSHA 30 CFR 72.710 (where applicable) requirements must be followed whenever workplace conditions warrant respirator use. **Other Information:** When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Pr	ор	ertie <u>s</u>
Physical State	:	Liquid
Appearance	:	Dark Blue
Odor	:	Pleasant
Odor Threshold	:	Not available
рН	:	10
Evaporation Rate	:	Not available
Melting Point	:	0 °C (32.00 °F)
Freezing Point	:	Not available
Boiling Point	:	100 °C (212.00 °F)
Flash Point	:	> 100 °C (212.00 °F)
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20 °C	:	Not available
Relative Density	:	1.005 (water = 1) at 20 °C (68 °F)
Specific Gravity	:	1.005 at 20 °C (68 °F)
Solubility	:	Soluble in water.
Partition Coefficient: N-octanol/water	:	Not available
Viscosity	:	Not available
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.
CECTION 10, CTARLITY AND REACTIVITY		

SECTION 10: STABILITY AND REACTIVITY

Reactivity: None known.

 Chemical Stability:
 Stable under recommended handling and storage conditions (see section 7).

 Possibility of Hazardous Reactions:
 Hazardous polymerization will not occur.

 Conditions to Avoid:
 Direct sunlight. Extremely high or low temperatures.

 Incompatible Materials:
 Strong oxidizers.

 Hazardous Decomposition Products:
 Carbon oxides (CO, CO₂). Sodium oxides. Sulfur compounds.

 SECTION 11: TOXICOLOGICAL INFORMATION

 Information on Toxicological Effects - Product
 Acute Toxicity: Not classified

 LD50 and LC50 Data: Not available
 Skin Corrosion/Irritation: Not classified Serious

Eye Damage/Irritation: Not classified.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: May cause mild skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
LD50 Oral Rat	2310 mg/kg	
LD50 Dermal Rabbit	6300 mg/kg	
Diethylaminoethanol (100-37-8)		
LD50 Oral Rat	1320 mg/kg	
LD50 Dermal Rabbit	1 ml/kg	
LC50 Inhalation Rat	5 (mouse)	

SECTION 12: ECOLOGICAL INFORMATION

<u>Toxicity</u>

Ecology - General: Harmful to aquatic life.

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
LC50 Fish 1	5 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])	
LC 50 Fish 2	12.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])	
Diethylaminoethanol (100-37-8)		
LC50 Fish 1	1660 - 1920 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	83.6 mg/l (Exposure time: 48 h - Species: Daphnia magna Straus)	
Persistence and Degradability Not available		
Bioaccumulative Potential		
Diethylaminoethanol (100-37-8)		
Log Pow	0.21 (at 23 °C)	

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

14.1. UN Number Not regulated for transport

- 14.2. UN Proper Shipping Name Not regulated for transport
- **14.3.** Additional Information Not regulated for transport

Transport by Sea Not regulated for transport

Air Transport Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Salt Off Concentrate

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Diethylaminoethanol (100-37-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

According to Federal Register / Vol. //, No. 58 / Monday, March 26, 2012 / Rules And Regulations
US State Regulations
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)
U.S Texas - Effects Screening Levels - Long Term
U.S Texas - Effects Screening Levels - Short Term
Diethylaminoethanol (100-37-8)
U.S Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S Idaho - Occupational Exposure Limits - TWAs
RTK - U.S Massachusetts - Right To Know List
U.S Michigan - Occupational Exposure Limits - Skin Designations
U.S Michigan - Occupational Exposure Limits - TWAs
U.S Minnesota - Hazardous Substance List
U.S Minnesota - Permissible Exposure Limits - Skin Designations
U.S Minnesota - Permissible Exposure Limits - TWAs
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S New Jersey - Right to Know Hazardous Substance List
U.S New York - Occupational Exposure Limits - Skin Designations
U.S New York - Occupational Exposure Limits - TWAs
U.S North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S Oregon - Permissible Exposure Limits - Skin Designations
U.S Oregon - Permissible Exposure Limits - TWAs
RTK - U.S Pennsylvania - RTK (Right to Know) List
U.S Tennessee - Occupational Exposure Limits - Skin Designations
U.S Tennessee - Occupational Exposure Limits - TWAs
U.S Texas - Effects Screening Levels - Long Term
U.S Texas - Effects Screening Levels - Short Term
U.S Vermont - Permissible Exposure Limits - Skin Designations
U.S Vermont - Permissible Exposure Limits - TWAs
U.S Washington - Permissible Exposure Limits - Skin Designations
U.S Washington - Permissible Exposure Limits - STELs
U.S Washington - Permissible Exposure Limits - TWAs
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
Canadian Regulations

Salt Off Concentrate

WHMIS Classification

Class D Division 2 Subdivision B - Toxic material causing other toxic effects



Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Diethylaminoethanol (100-37-8)		
Listed on the Canadian DSL (Domestic Sustances List)		
Listed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 1 %		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

WHMIS Classification	Class B Division 3 - Combustible Liquid
	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects
	Class E - Corrosive Material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date Other Information : 01/21/2015

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

in Text Phrases:			
	Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
	Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
	Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Cate	
	Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Cate	
	Eye Dam. 1	Serious eye damage/eye irritation Category 1	
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A	
	Flam. Liq. 3	Flammable liquids Category 3	
	Skin Irrit. 2	Skin corrosion/irritation Category 2	
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
	H226	Flammable liquid and vapor	
	H302	Harmful if swallowed	
	H315	Causes skin irritation	
	H318	Causes serious eye damage	
	H319	Causes serious eye irritation	
	H332	Harmful if inhaled	
	H335	May cause respiratory irritation	
	H401	Toxic to aquatic life	
	H402	Harmful to aquatic life	
NFPA Health Hazard	: 1 - Exposure could cause irritation injury even if no treatment is give		
NFPA Fire Hazard	: 1 - Must be preheated before ignition can occur.		
NFPA Reactivity	: 0 - Normally stable, even under fire exposure conditions, 1 0 and are not reactive with water.		

Party Responsible for the Preparation of This Document DONOVAN MARINE INC.

1-800-347-4464

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS